

POLYMER BASED TILE ADHESIVE

DESCRIPTION:

Improved performance cementations adhesive for any kind of tiles

D+ GOLD 3000 is a no slip, high adhesion quartz adhesive. It can be applied up to 10 mm bed thickness high dispersion copolymers hydraulic binders composed of only cement clinker. **D+ GOLD 3000** provides rheological mixture for a prolonged stability. It serves purpose of high resistance laying on flooring and wall of ceramic and homogeneous tiles and glass mosaic on cement based substrates.

Features & Benefits

- High strength bond
- No odour
- Economical
- Water cleanable
- Easy to spread
- Interior use for wall and floor
- Thick & thin bed application

Area of Application:

- Non toxic
- Laying absorbing ceramic files
- On indoor and outdoor
- On walls and floors
- Spot-gluing insulting panels made of polystyrene, polyurethane foam, rock or glass wool.

Mixed with D+ PREMIUM SBR 111(250gm-500gm/bag) can be utilized for:

- Tiling porcelain stoneware in large formals on indoor and out door
- Tiling natural stone and marble, so long as they are not affected by water of liable to stain.
- Tiling on water or electric heated screeds

POLYMER BASED TILE ADHESIVE

- Tilling on swimming pools

CERTIFIED

- C2TE GARDE

Technical Specification:

Chemical base	Portland cement, selected aggregates, water retention additives And re-dispersible polymer.
Density	fresh mortar density: ~1.5 kg/l
Shear Strength	1200 kN/m ²
Tensile Strength	1000 kN/m ²
Grading	Dmax:0.5 mm
Bed Thickness	3 to 10mm
Pot life	≥4 hrs at 23o c
Curing time	≥3 min at 23o c
Open time	≥30 minutes at 23o c
Adjustability time	≥45 min 23o c
Grouting	8 hr on wall/~24 hr on floor

Consumption:

The consumption is dependent on the surface profile and roughness of the substrate as well as on the tiles and the placing technique (simple placing or back-buttering). Approximately 55 to 60 sq. ft for 20 kgs. Bag with 6mm × 6mm square notch trowel for a bed of 3 mm.

DISCLAIMER Information provided on this data sheet is the guideline for usage. Users are advised to undertake a trial for product suitability prior to its full scale usage. There is no implied guaranty / warranty for the results and the company is not liable for any consequential damages.

D FIX ENTERPRISE

506,Parshwanath Business Park, Nr. Prahladnagar Garden, Satellite, Ahmedabad-380015
Ph.: 079- 40022816,+91-7572963387•Email:customercare@dfix.co.in•Web-www.dfix.co.in