

D+ Leakproof is 100% pure acrylics (elastomeric), fiber reinforced single coat ready to use product with excellent mechanical strength, crack bridging. Upon Curing It forms a thick, seamless, durable film resulting good waterproofing system

Product Advantages:

- Single pack ready to use
- Good mechanical strength
- Good adhesion strength with concrete /tiles /china mosaic /masonry surface
- 100% Pure acrylic based with high seen in white colour results high level reflectance.
- Excellent Water impermeability
- Anti-Carbonation Coating & UV stable product

PHYSICAL PROPERTIES

- | | |
|---|----------------------------|
| • <i>Color</i> | White |
| • <i>Form</i> | 1 component |
| • <i>Specific Gravity</i> | 1.1 |
| • <i>Tensile Strength</i> | >1.5N / mm ² |
| • <i>Elongation at Break</i> | >150% |
| • <i>Adhesion Strength (concrete)</i> | >1.5N / mm ² |
| • <i>Adhesion Strength (tiles/China Mosaic)</i> | >1N / mm ² |
| • <i>Touch Dry</i> | After 4hour |
| • <i>Cure Time</i> | 24 hours approx. |
| • <i>Crack Bridging</i> | >1 mm |
| • <i>Base</i> | >Water based pure acrylics |

Coverage :

For concrete surface /China Mosaic recommended consumption is 1.1 lit /SQM & for vertical wall consumption is 0.5 Lit/SQM

STORAGE

- Store between temperatures of + 5°C and 40°C. Keep containers closed when not in use.

SELF-LIFE

- Self-life: 12 month from data of manufacturing provided stored under shade, away from direct heat and sunlight and well protected from freezing

*All recommendations for use of our products, whether given by us in writing, verbally are to be implied, from the results of tests carried out by us, based on the current state of our knowledge. Although the information contained in this sheet is accurate to the best of our knowledge, no liability can be accepted in respect of such information and no warranty or conditions are intended in respect of the products described, as the conditions of application are beyond our control.

506 Parshwanath Business Park, Nr. Prahladnagar Garden, Satellite, Ahmedabad-380015

- Ph.: 079- 40022816,+91-7572963387
- Email: customercare@dfix.co.in •Web: www.dfix.co.in