

D+ TERRASEAL 007 (S/B)

Clear Waterproofing Coating for Terrace, China Mosaic & Natural Stone Color Enhancer.

**DESCRIPTION:**

Terraseal is an elastic, transparent acrylic UV resistance TPR base that provides resistance to weathering, Low foot traffic use for china mosaic terrace, glass mosaic tiles & natural stone, On Concrete & Paver Block as a color enhancer.

AREA OF APPLICATION:

For waterproofing of China mosaic and Glass mosaic, clear coat for stone & non-ferrous metal, for protection & color enhance.

FEATURES & BENEFITS:

- Excellent adhesion to glazed, ceramic surfaces and china mosaic.
- Crack bridging ability.
- Good abrasion resistance and resistance to weathering and UV.
- Provides glossy finish to china mosaic.
- Clear transparent coating.
- Easy to apply, Ready to use –Single Component.
- Resistance to low foot traffic.
- Offers waterproofing properties.

METHOD OF APPLICATION:

Surface Preparation Ensure that the surface to be painted is free from rust, grease, oil & loose material before application of TERRASEAL 007 (S/B).

APPLICATION:

After proper surface preparation by cleaning, apply first coat of TERRASEAL 007 (S/B). UV resistance coating by brush or roller depending on surface 30 to 40 micron thickness on the surface of application without any dilution. Allow drying for 5 to 6 hours and then apply 2nd coat in perpendicular direction of first coat and leave it for 24 hrs to hard dry.

TECHNICAL INFORMATION

TECHNICAL INFORMATION			
Test Parameters	Requirement	Test Parameters	Requirement
Appearance	Clear transparent liquid	Elongation	Good Elongation
Chemical base	Specially formulated acrylic polymer	Density @ 27 °C	1.1
Viscosity @ 27 °C	40 sec ford cup		

COVERAGE : 40 to 50 Sq. Ft. /per Ltr. / coat

Packing: 1 Ltr, 5 Ltr and 25 Ltr .

HEAD OFFICE:

506, Parshwanath Business park, opp
Prahlanagar garden, SG highway, Ahmedabad,
Gujarat, India. 380015

D+ TERRASEAL 007 (S/B)

Clear Waterproofing Coating for Terrace, China Mosaic & Natural Stone Color Enhancer.



STORAGE & LIFE:

Best before 12 month from the date of manufacture when in sealed pack and stored in cool & dry place in unopened condition away from direct sunlight & fire (Flammable).

HEALTH AND SAFETY PRECAUTIONS:

- Use rubber hand gloves & safety goggles, while using TERRASEAL 007 (S/B).
- In case of contact with skin, wash with plenty of water.
- Keep children out from reach.

TECHNICAL INFORMATION & SERVICES:

Further information and advice, including practical demonstration are freely available with the Technical Service Department of DFIX ENTERPRISE - AHMEDABAD.

CONDITIONS OF SALE:

Sold subject to the Company's conditions of sale which are available on request.

NOTE The information supplied in this datasheet is based upon extensive experience and is given in good faith in order to help you. Our Company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products; however as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof.

HEAD OFFICE:

506, Parshwanath Business park, opp
Prahlnadnagar garden, SG highway, Ahmedabad,
Gujarat, India. 380015

D FIX ENTERPRICE I Mo. No. +91 75729 63387
customercare@dfix.co.in I www.dfixindia.com